



DLS Startup Report

Startup Date:

Install Date:

Tech Name:

Equipment Brand:

Single Zone:

Multi-Zone:

Carrier Enterprise Technical Services

Site Name:

Contractor:

Address:

Address:

City, State:

City, State:

Zip:

Zip:

Contact:

Contact:

Phone:

Phone:

Outdoor Unit Md.:

Serial:

Indoor Unit #A Md.:

Serial:

Indoor Unit #B Md.:

Serial:

Indoor Unit #C Md.:

Serial:

Indoor Unit #D Md.:

Serial:

Indoor Unit #E Md.:

Serial:

Indoor Unit #F Md.:

Serial:

Outdoor Temp at Startup: °F

Indoor Temp at Startup: °F

Additional Refrigerant Charge Amount Added: oz.

Cooling Mode – High Pressure: PSIG / Low Pressure: PSIG

Heating Mode – High Pressure: PSIG / Low Pressure: PSIG

Note: Measure after 20 min. of operation, not all units have both refrigerant connections. If Multi put all in Heat or all in Cool mode for readings.

Incoming Power Supply: L1-L2	Volts / L1-G	Volts / L2-G	Volts
Indoor Unit #A L1-L2	Volts \ Voltage Range L2-S: Top	Volts+ / Bottom	Volts-
Indoor Unit #B L1-L2	Volts \ Voltage Range L2-S: Top	Volts+ / Bottom	Volts-
Indoor Unit #C L1-L2	Volts \ Voltage Range L2-S: Top	Volts+ / Bottom	Volts-
Indoor Unit #D L1-L2	Volts \ Voltage Range L2-S: Top	Volts+ / Bottom	Volts-
Indoor Unit #E L1-L2	Volts \ Voltage Range L2-S: Top	Volts+ / Bottom	Volts-
Indoor Unit #F L1-L2	Volts \ Voltage Range L2-S: Top	Volts+ / Bottom	Volts-

Additional Comments / Service Settings Performed: